

Multifunction meters

PAN Multicar

Digital Automotive Multimeter

- LCD display with bargraph 20 mm
- **Backlight**
- Diode test
- Data Hold
- **Peak value memory (peak memory)**
- Auto power off

Scope of delivery: test leads, Operating manual, Type-K temperature probe, suitcase



Technical Data	PAN Multicar
Duty-cycle	0,5 - 99 %
DC voltage (V =)	0,1 mV - 600 V
AC voltage (V ~)	0,1 mV - 600 V
DC current (A =)	0,01 mA - 20 A
AC current (A ~)	0,01 mA - 20 A
Resistance (Ω)	0,1 Ω - 40 M Ω
Frequency (Hz)	0,001 Hz - 10 MHz
Capacitance (F)	0,01 nF - 40 mF
Infrared - Temperature measurement ($^{\circ}$ C)	-20 $^{\circ}$ C - +280 $^{\circ}$ C
Temperature ($^{\circ}$ C) (type K probe)	-20 $^{\circ}$ C - +1000 $^{\circ}$ C
Continuity test (•)))	<35 Ω
Accuracy (%)	0,5 % - 3 %
Dimensions	182 x 82 x 55 mm
Weight (gross / net)	2.219 / 393 g
Required battery(s):	1x 9V 6LR61
Measuring category (CAT)	CAT III 250 V