

## Multifunction meters

### PAN Multicar

#### Digital Automotive Multimeter

- LCD display with bargraph 20 mm
- **Backlight**
- Data Hold
- **Peak value memory (peak memory)**
- Diode test
- Auto power off

**Scope of delivery:** test leads, Type-K temperature probe, suitcase, Operating manual



Technical Data	PAN Multicar
DC voltage (V =)	0,1 mV - 600 V
AC voltage (V ~)	0,1 mV - 600 V
DC current (A =)	0,01 mA - 10 A
AC current (A ~)	0,01 mA - 10 A
Resistance ( $\Omega$ )	0,1 $\Omega$ - 40 M $\Omega$
Continuity test (•)))	<35 $\Omega$
Frequency (Hz)	0,001 Hz - 10 MHz
Duty-cycle	0,5 - 99 %
Capacitance (F)	0,01 nF - 40 mF
Temperature ( $^{\circ}$ C) (type K probe)	-20 $^{\circ}$ C - +1000 $^{\circ}$ C
Accuracy (%)	0,5 % - 3 %
Dimensions	182 x 82 x 55 mm
Weight (gross / net)	2.219 / 393 g
Required battery(s):	1x 9V 6LR61
Measuring category (CAT)	CAT III 600 V